

SAVER™

Field instruments

Product guide



Measurement instruments

Do you know what kind of hazards your product is being exposed to? When products are damaged while being manufactured, shipped, or used, the only effective way to uncover the cause is by using optimized field data recording practices and a high quality data logger.

Lansmont offers two primary categories of Field Instruments: Measurement and Monitoring. Step 1 of Lansmont's Six Step Method calls for Defining of the Environment. Measurement Instruments provide the ability to record nearly everything that occurs during a recording session. Lansmont Measurement Instruments store up to tens of thousands of events, which can be used to clearly assess, characterize, and define various environments.


		SAVER™ 3D15	SAVER™ 3X90	SAVER™ 9X30
				
		Ideal for low-frequency dynamics, which may occur in aerospace, amusement park rides, rail impacts, crash recording, brake testing, and others.	Characterizing complete dynamic and environmental conditions (temperature and humidity) as they exist in longer-term transport conditions.	Same as 3X90 with external dynamic channel connections and the ability to seamlessly link all data to GPS location, all in one data file.
Size		3.7 x 2.9 x 1.7 in. (95 x 74 x 43 mm)	3.7 x 2.9 x 1.7 in. (95 x 74 x 43 mm)	5.0 x 4.9 x 1.7 in. (127 x 124 x 43 mm)
Weight		16.7 oz. (473 g)	16.7 oz. (473 g)	35.0 oz. (1 kg)
Triggering		threshold and timer	threshold and timer	threshold and timer
Memory		128 MB	128 MB	128 MB
Programmable Sampling		50-5,000 samples per second	50-5,000 samples per second	50-10,000 sample per second
Programmable Filtering		10, 20, 25, 50, 100, 200, 250, 500 Hz	10, 20, 25, 50, 100, 200, 250, 500 Hz	10, 20, 25, 50, 100, 200, 250, 500 Hz external channels: 1,000, 2,000, 2,500 Hz
Continuous Record Time		15 days	90 days	30 days
Accelerometer Type		triax MEMS	triax piezoelectric	triax piezoelectric
Accelerometer Range		50 g	200 g	200 g
3dB Frequency Response		DC to filter maximum	0.4 Hz. to filter maximum	0.4 Hz. to filter maximum
Data	Shock	✓	✓	✓
	Vibration	✓	✓	✓
	Temperature	✓	✓	✓
	Humidity	✓	✓	✓
	Atmospheric Pressure			✓
	GPS Location	able to import external data	able to import external data	optionally embedded in 9X-GPS
	External Acceleration Channels			6 programmable

Monitoring instruments

Step 2 of Lansmont’s Six Step Method calls for Defining a Product’s Fragility. How many G’s can the product withstand, how much velocity change, and at what frequencies do the product’s components resonate? That information serves as the benchmark to which one can compare with field data captured with Monitoring Instruments. With monitoring, the focus is clear. Typically only data that exceeds predetermined threshold/severity/fragility levels is captured.

Lansmont offers the industry’s most robust line of unattended, battery operated data loggers, as well as turnkey transportation monitoring services to fulfill your field data acquisition requirements. We’re the leader in this highly specialized field and we offer sophisticated products and services to assist your company in its efforts.

		SAVER™ AM
		 Monitoring for critical shock events, as well as temperature, humidity and atmospheric pressure, light and orientation data – providing corresponding LED alarm indicators for all critical data.
Size		2.8 x 3.6 x 1.3 in. (71 x 91 x 33 mm) w/flanges
Weight		10 oz. (283 g)
Triggering		threshold acceleration and timer environmental
Memory		400 largest threshold events, 10,000 timer events
Programmable Sampling		500-3,000 samples per second
Programmable Filtering		50, 100, 250, 300 Hz
Continuous Record Time		30 days
Accelerometer Type		triax piezoelectric
Accelerometer Range		100 g or 200 g (selectable)
3dB Frequency Response		0.5 Hz to filter maximum
Data	Shock	✓
	Vibration	✓
	Temperature	✓
	Humidity	✓
	Atmospheric Pressure	✓
	Orientation	✓
	Light	✓
	GPS Location	able to import external data



lansmont.com

17 Mandeville Court, Monterey, CA 93940 +1-831-655-6600

Lansmont reserves the right to alter equipment specifications without prior notice. E&OE 05/2023